

# System: Command Line Arguments

---

**CPSC 217: Introduction to Computer Science for Multidisciplinary Studies I**  
**Jul 2021 - CBE**

Jonathan Hudson, Ph.D.  
Instructor  
Department of Computer Science  
University of Calgary

Wednesday, June 2, 2021

*Copyright © 2021*



# Command Line Arguments

---

# Command-line Arguments

---

- You can pass 0, 1 or more command-line arguments to a Python program

```
>python programName.py
```

```
>python programName.py arg1
```

```
>python programName.py arg1 arg2
```

```
>python programName.py arg1 arg2 ...
```

# Command-line Arguments

---

- The arguments must be separated by space.
- If one of the arguments contain a space (a string containing spaces), then you must surround it with double quotes.
- The program accesses these arguments through ***argv*** from the ***sys*** package
- ***argv*** (**argument values**) is a list of the passed arguments.

# Command-line Arguments

---

```
>python myProgram.py 1 string "string string"
```

↓  
sys.argv[0]

↓  
sys.argv[1]

↓  
sys.argv[2]

↓  
sys.argv[3]

# Command-line Arguments

---

```
import sys
msg = 'Passed %d arguments. These are: %s' % (len(sys.argv), sys.argv)
print(msg)
```

# Command-line Arguments

---

```
import sys
msg = 'Passed %d arguments. These are: %s' % (len(sys.argv), sys.argv)
print(msg)
```

```
>python myProgram.py 1 string "string string"
```



First argument is always the module name

```
Passed 4 arguments.
These are: ['myProgram.py', '1', 'string', 'string string']
```

# Command-line Arguments

---

- You can access individual arguments using indices or by iterating through *argv*.

```
>python myProgram.py 1 string "string string"
```

```
import sys
print(sys.argv[0])#first argument

for arg in sys.argv:#print all arguments
    print(arg)
```



```
myProgram.py
myProgram.py
1
string
string string
```



# Errors

---

# Command-line Arguments

---

- When accessing arguments using index, you must be careful not to use an index that is outside the range of the list.
  - Otherwise, an error will occur.

```
>python myProgram.py 1 string "string string"
```

```
from sys import argv
i = 0
while i <= len(argv):
    print(argv[i])
    i+=1
```



```
myProgram.py
1
string
string string
Traceback (most recent call last):
  File "myProgram.py", line 4, in <module>
    print(argv[counter])
IndexError: list index out of range
```

# Command-line Arguments

---

- To ensure that an argument is within the range of the *argv* list, use the *len()* function:

```
>python myProgram.py "New Argument"
```

```
import sys
if len(sys.argv) != 2:
    print('Invalid number of arguments')
else:
    value1 = sys.argv[1]
    print("Received", value1)
```

One argument is expected (in addition to the module name)

# Design

---

# Good Program Design

---

- Check if argument count is correct
  - If not then end program with error message
- Check if argument data is correct
  - If not then end program with error message
- Check if files can be opened?
  - Next topic

# Onward to ... files.

---

Jonathan Hudson  
[jwhudson@ucalgary.ca](mailto:jwhudson@ucalgary.ca)  
<https://pages.cpsc.ucalgary.ca/~hudsonj/>

